

SLIDING SYSTEM NON INSULATED



SMARTIA M14600 is ALUMIL's brand new sliding system with extremely elegant straight lines, incorporating all the expertise of ALUMIL Group. It meets the modern architectural trends and the requirements for especially high performance and is the ideal solution for sliding systems in areas with warmer climates.

- Basic depth of sash 35 mm
- Minimum visible interlock width of only 23 mm so as to maximize visibility and natural lighting
- Special interlocking profile with integrated handle for functionality and significant wind load resistance (optional)
- Sash profiles available for 45° and 90° assembling
- Meeting stile width of just 62 mm
- Vast range of typologies compatible with various mechanisms
- Max Glass thickness up to 25 mm and weight per sash up to 200 Kg
- Smooth and easy sliding thanks to inox rails





























TECHNICAL CHARACTERISTICS


Visible aluminium face width	95,5 mm
Frame height	31,5 / 40,0 mm
Frame width	92,0 / 143,0 mm
Sash height	67 / 79 mm
Sash width	35 mm
Interlocking profile width	23 / 68,5 / 80,5 mm
Sash weight	up to 200 Kg
Glazing	up to 25 mm

TYPOLOGIES


Horizontal sliding




Two sash sliding window



Two sash sliding window with fly screen



Three sash sliding window



Single sash sliding window with fix pane



Two sash parallel sliding window 900 cutting



Three sash sliding window with fly screen



Two sash sliding window 90° cutting, with fly screen



Single sash sliding window with fix pane 90° cutting


Meeting stile



Four sash meeting stile window



Four sash meeting stile window 90° cutting




Six sash meeting stile window



Six sash meeting stile window 90° cutting

Sliding into wall cavity



Single sash sliding window with shutter



Two sash sliding window with shutter



Single sash sliding window, with fly screen & shutter



Two sash sliding window, with fly screen & shutter

ALUMIL SA

KILKIS INDUSTRIAL AREA GR 61 100, KILKIS TEL: +30 23410 79300 FAX: +30 23410 71988 www.alumil.com